




General description

Symbol	Value
$V_R @ T_C=25^{\circ}\text{C}$	Min 1200V
$I_F @ T_C=150^{\circ}\text{C}$	40A
Q_C	Typ 241nC




Package



Features

- 175°C Maximum operating temperature
- Negligible reverse recovery current.
- Fast switching speed



Applications

- General purpose
- Switching mode power supply
- Boot diodes in PFC at DC/DC
- Industrial motor drives
- Motor drivers
- Solar inverters



Maximum ratings ($T_C = 25^{\circ}\text{C}$)

Parameter	Symbol	Test condition	Value	Units
Repetitive peak reverse voltage	V_{RRM}	-	1200	V
DC peak reverse voltage	V_R	-	1200	V
Continuous forward current	I_F	$T_C=150^{\circ}\text{C}$	40	A
Non-repetitive forward surge current	I_{FSM}	$T_C=25^{\circ}\text{C}, t_p=10\text{ms}$	225	A
Power dissipation	P_D	$T_C=25^{\circ}\text{C}$	556	W
Operating and storage temperature range	T_J, T_{stg}	-	-55 to 175	$^{\circ}\text{C}$







Electrical characteristics ($T_C = 25^\circ\text{C}$)

Parameter	Symbol	Test condition	Value			Units
			Min	Typ	Max	
Forward voltage	V_F	$I_F=40\text{A}, T_C=25^\circ\text{C}$	-	1.4	1.7	V
		$I_F=40\text{A}, T_C=175^\circ\text{C}$	-	1.8	-	V
Reverse current	I_R	$V_R=1200\text{V}, T_C=25^\circ\text{C}$	-	-	100	μA
		$V_R=1200\text{V}, T_C=175^\circ\text{C}$	-	-	300	μA
Total capacitive charge	Q_C	$V_R=800\text{V}$	-	241	-	nC
Total capacitance	C	$V_R=1\text{V}, f=100\text{kHz}$	-	2,638	-	pF
		$V_R=800\text{V}, f=100\text{kHz}$	-	165	-	pF




Thermal characteristics($T_C = 25^\circ\text{C}$)

Symbol	Parameter	Typ	Max	Units
$R_{th(j-c)}$	Junction to case	-	0.27	$^\circ\text{C}/\text{W}$




 Typical electrical characteristics curves ($T_C = 25^\circ\text{C}$)


$V_F - I_F$ Characteristics




$V_R - I_R$ Characteristics




$T_C - I_p$ Characteristics



$V_R - C$ Characteristics




$V_R - Q_C$ Characteristics





Package dimensions(TO-247-2L)

[Unit : mm]



Symbol	Min	Typ	Max
A	4.80	5.00	5.20
A1	2.29	2.36	2.54
A2	1.90	2.00	2.10
b	1.10	1.20	1.30
b1	1.91	2.11	2.20
c	0.50	0.60	0.70
D	20.80	21.07	21.34
D1	17.43	17.63	17.83
E	15.75	15.94	16.13
E1	13.06	13.26	13.46
E2	4.32	4.58	4.83
e	5.45 BSC		
L	19.85	20.00	20.25
L1	-	-	4.49
ΦP	3.55	3.60	3.65
Q	5.59	5.89	6.19
S	6.15 BSC		



Marking information

